

Aluminium Casement Windows

Slimline and high-performance aluminium casement windows with clean sightlines and strong thermal and acoustic options.

SPECIFICATION

| | |
|------------------------|---|
| Thermal | Whole-window U-values from 0.85 W/m ² K where specified |
| Size and weight | Sashes up to 1.3 m × 2.4 m at up to 160 kg where specified |
| Security | PAS 24 tested-security routes |
| Glazing | Double, triple and acoustic units up to 55 mm, project-specified |
| Finishes | Full RAL, dual-colour and anodised-style finishes |
| Configurations | Flush or standard sash, French casement, fixed lights and combinations |
| Weather | Air permeability Class 4, watertightness to Class E1800, wind resistance to Class C5; acoustic up to Rw 46 dB |

STANDARDS AND CONFORMITY

PAS 24 security routes, BS EN 14351-1 (windows and doors) and BS EN 13830 (curtain walling), with UKCA marking and Declaration of Performance support where specified.

BEST FOR

- Trade installers
- Builders
- Architects & specifiers

VitrineAlu Ltd Unit 1 Nassau Business Park, Bahama Road, Haydock, St Helens, Merseyside, WA11 9FW
0330 133 3622 info@vitrinealu.co.uk vitrinealu.co.uk

Figures are achievable capability, confirmed against the selected system and the project specification at quote. Trade supply across North West England.