

Aluminium Curtain Walling

Thermally broken aluminium curtain walling for commercial facades, entrances and large glazed screens.

SPECIFICATION

| | |
|------------------------|--|
| Thermal | Ucw from 0.6 W/m ² K where specified |
| Size and weight | Facade units up to 1.5 m × 3.6 m at up to 350 kg, 66 mm sight line where specified |
| Security | BS EN 13830 / UKCA / DoP support; PAS 24 and RC2 routes where specified |
| Glazing | Project-specified insulated glass units up to 58 mm |
| Finishes | Full RAL, wood-effect and textured routes |
| Configurations | Stick-system mullion/transom for facades, screens and entrances |

STANDARDS AND CONFORMITY

PAS 24 security routes, BS EN 14351-1 (windows and doors) and BS EN 13830 (curtain walling), with UKCA marking and Declaration of Performance support where specified.

BEST FOR

- Commercial teams
- Architects & specifiers
- Main contractors

VitrineAlu Ltd Unit 1 Nassau Business Park, Bahama Road, Haydock, St Helens, Merseyside, WA11 9FW
0330 133 3622 info@vitrinealu.co.uk vitrinealu.co.uk

Figures are achievable capability, confirmed against the selected system and the project specification at quote. Trade supply across North West England.