

Aluminium Heritage Doors

Steel-look aluminium heritage doors for classic sightlines with modern thermal performance and security.

SPECIFICATION

Thermal	Whole-window U-values from 1.0 W/m ² K where specified
Size and weight	Sashes up to 1.8 m × 1.8 m at up to 100 kg, slim 37 to 48 mm frame faces where specified
Security	PAS 24 tested-security routes
Glazing	Double or triple glazing up to 44 mm, project-specified
Finishes	RAL, dual-colour and anodised-style routes
Configurations	Single and double doors, heritage bar layouts, low-threshold option
Weather	Air permeability Class 4, watertightness to Class E1200, wind resistance to Class CE2400; acoustic up to Rw 45 dB

STANDARDS AND CONFORMITY

PAS 24 security routes, BS EN 14351-1 (windows and doors) and BS EN 13830 (curtain walling), with UKCA marking and Declaration of Performance support where specified.

BEST FOR

- Trade installers
- Builders
- Architects & specifiers

VitrineAlu Ltd Unit 1 Nassau Business Park, Bahama Road, Haydock, St Helens, Merseyside, WA11 9FW
0330 133 3622 info@vitrinealu.co.uk vitrinealu.co.uk

Figures are achievable capability, confirmed against the selected system and the project specification at quote. Trade supply across North West England.