

Aluminium Sliding & Patio Doors

Slim-sightline sliding and lift-and-slide aluminium doors for big glass that moves with control.

SPECIFICATION

Thermal	Whole-unit U-values from 1.0 W/m ² K where specified on high-performance lift-and-slide routes
Size and weight	Sashes up to 2.2 m × 2.87 m at up to 420 kg where specified
Security	Tested-security routes where required
Glazing	Double, triple, laminated and integral-blind units, 24 to 48 mm, project-specified
Finishes	Full RAL, dual-colour and wood-effect routes
Configurations	Two or three track, 2/3/4/6 sashes, 35 mm slim interlock, pocket and corner options
Weather	Air permeability Class 4, watertightness to Class 8A, wind resistance to Class C5; acoustic reduction up to 45 dB

STANDARDS AND CONFORMITY

PAS 24 security routes, BS EN 14351-1 (windows and doors) and BS EN 13830 (curtain walling), with UKCA marking and Declaration of Performance support where specified.

BEST FOR

- Trade installers
- Builders
- Architects & specifiers

VitrineAlu Ltd Unit 1 Nassau Business Park, Bahama Road, Haydock, St Helens, Merseyside, WA11 9FW
0330 133 3622 info@vitrealu.co.uk vitrealu.co.uk

Figures are achievable capability, confirmed against the selected system and the project specification at quote. Trade supply across North West England.